

RBT35 SERIES REAR BLADES

HP REQUIRED
35-80 HP

HITCH
Cat. 1 & 2




DIRTWORKING

The perfect all-around blade.

Our RBT35 Series Blade is just right for use in landscape, construction, farming or snow removal. Looked upon as the perfect all-around blade, the RBT35 Series is offered with optional hydraulic function for tilt, offset and angle.



The 3" kingpin on the moldboard is stout enough to hold up to tough tasks.

	RBT3584	RBT3596
Horsepower	2WD: 35-80 HP 4WD: Up to 65 HP	
Hitch	Cat. 1 & 2	
Working Width (cm)	84" (213)	96" (244)
Weight - lb (kg)	709 (322)	745 (338)
Maximum G.V.W. - lb (kg)	9,500 (4,318)	
Blade Angle	9 Positions (Manual): Up to 50° Fwd & Rev (Hydraulic)	
Tilt	Up to 20°	
Tilt Cylinder	2" x 6" x 1-1/4"	
Swing Offset	Up to 30° Left and Right	
Offset Cylinder	3-1/2" x 14" x 1-1/4"	
Moldboard Height	17"	
Moldboard Thickness	5/16" with 3/16" Tapered Reinforcement Channel	
Cutting Edge	1/2" x 6", Reversible & Replaceable; Heat Treated	
Options	Skid Shoes, End Plates Gauge Wheel, Double Selector Valve, Cushion Valve	
Colors		

Quick Hitch
SYSTEM

RBT45/55 SERIES REAR BLADES

HP REQUIRED
70-180 HP

HITCH
Cat. 2 & 3



DIRTWORKING

Built tough...where it really counts.

Land Pride's RBT45 and RBT55 Series 3-Way Hydraulic Rear Blades are ideal for landscaping, construction, snow removal, feedlot cleaning, and all-around farm use. Make changes on the go with hydraulics at all three positions and use your time more efficiently. Available options include single or double hydraulic gauge wheels, side plates for holding dirt in, and skid shoes for blade protection.



Shown with optional end plates.



Pivot weldment features a 1" thick plate steel turntable, 3/4" thick tilt pivot bushing and a 4" solid kingpin.



Optional cushion valve on the RBT45 protects cylinders and blade components during extreme impacts.



Optional single or dual gauge wheels add accuracy and simplify grading operations.

	RBT4596	RBT45108	RBT55120
Horsepower	70-125 HP		90-180 HP
Hitch	Cat. 2 & 3		Cat. 2 & 3
Working Width (cm)	96" (244)	108" (274)	120" (304)
Weight - lb (kg)	1,130 (513)	1,166 (529)	1,753 (795)
Maximum G.V.W. - lb (kg)	9,500 (4309)		15,000 (6818)
Blade Angle	Fwd & Rev Up to 45°		Fwd & Rev Up to 45°
Angle Cylinder	4" x 16"	4-1/2" x 16" x 2"	
Tilt	Up to 15°		Up to 30°
Tilt Cylinder	3" x 6" x 1-1/4"	3" x 8" x 1-1/4"	
Swing Offset	Up to 35" Left and Right		33"
Offset Cylinder	4" x 16"	4-1/2" x 16" x 2"	
Moldboard Height	19"		19"
Moldboard Thickness	5/16" with 1/4" Boxed Reinforcement		5/16" with 1/4" Boxed Reinforcement
Cutting Edge	1/2" x 6", Reversible & Replaceable; Heat Treated		1/2" x 6", Reversible & Replaceable; Heat Treated
Options	Skid Shoes, End Plates, Single or Dual Gauge Wheel, Cushion Valve, Double Selector Valve		Skid Shoes, End Plates, Hardened Wear Plates, Hydraulic Single Gauge Wheel, Hydraulic Dual Gauge Wheel, Double Selector Valve
Colors			

QuickHitch
SYSTEM

*See dealer for complete warranty information.

www.landpride.com

69