

SC40 SKID CUTTERS



AVAILABLE FOR: SSV65 / SSV75 / SVL65-2 / SVL75-3 / SVL97-2

- 4" Diameter cut capacity
- 1/4" Deck thickness
- Pressure gauge
- Tapered full length skid shoes

Farmers and ranchers, developers, contractors, and land owners can clear land or small trees, shrubs, bushes, and grass.



Easy-to-read pressure gauge allows the operator to ensure that the motor is operating at proper psi.

		SC4060	SC4072
Cutter Weight (kg) w/skid shoes and w/o front roller wheels		1,361 lbs (617)	1,680 lbs (762)
Cutting Width (m)		61.5" (1.56)	73.5" (1.87)
Overall Width (m)		72" (1.83)	84.5" (2.15)
Overall Length (m)		78" (1.98)	89" (2.26)
Cutting Capacity (cm)		4" (10.2) Diameter	
Drive Motor	Standard (lpm)	15-26 gpm flow (56.8-94.6)	
	High Volume (lpm)	27-43 gpm flow (98.4-162.8)	
Deck Thickness (mm)		1/4" (6)	
Side Skirt Construction (mm)		1/4" (6)	
Blade Carrier (mm)		Heavy-duty round 5/8" (16) plate	
Deck Wear Protection		Four corner mounted skid shoes and two mid skid shoes	
Blade Size (mm)		Heavy-duty round 5/8" (16) plate	
Skid Shoes Construction (mm)		3/8" (10) Plate	
Blade Size (cm)		1/2" x 5" (1.3 x 12.7) Bi-directional	
Blade Tip Speed	15-26 gpm Motor (mps/lpm)	14,455 fpm (73.4) at 26 gpm (94.6)	17,345 fpm (88) at 26 gpm (94.6)
	27-43 gpm Motor (mps/lpm)	15,440 fpm (78.4) at 43 gpm (162.8)	18,527 fpm (94.1) at 43 gpm (162.8)
Deck Lift Height Protection		Height adjustment safety chain	