

SC70 SKID CUTTERS



AVAILABLE FOR: SVL95-2s


- 7" Diameter cut capacity
- 1/4" Deck thickness
- 4 Swinging blades, reversible
- Replaceable carbide teeth on bottom of blade carrier
- Patent pending retractable front door
- Wide, angled full length skid shoes

Contractors and developers with extreme ground-clearing needs will easily eliminate brush and trees up to 7" in diameter.



Patent pending bi-folding retractable front door will fold open when cutting brush and trees. Covers the cutting chamber when not operating in extreme conditions.

	SC7072
Cutter Weight w/skid shoes (kg)	2,580 lbs (1,170)
Cutting Width (m)	73-1/2" (1.87)
Overall Width (m)	84-3/8" (2.14)
Overall Length (m)	92-1/4" (2.34)
Cutting Capacity (cm)	7" (17.78) Diameter
High Volume Drive Motor (lpm)	26-43 gpm flow (98.4-162.8)
Hydraulic Pressure	Up to 3500 psi
Deck Thickness (mm)	1/4" (6)
Side Skirt Construction (mm)	1/4" (6)
Blade Carrier (mm)	Two round 1/2" (12.7) plate weldments
Blade Size (mm)	3/4" (19.05) Double edge
Blade Tip Speed (mps/lpm)	14,870 fpm (75) at 43 gpm (162.8)
Skid Shoes Construction (mm)	3/8" (10) Plate
Front Deck Protection	Bi-fold door w/single row chain guard
Deck Lift Height Protection	Height adjustment safety chain
Mulching Teeth (mm)	3/4" (19.05) SQ carbide



Push bar forces trees away from the operator.



Replaceable carbide teeth on bottom of blade carrier.

SC7072 Skid Cutter

Specifications & Capacities		
Cutter weight with skid shoes	lbs (kg)	2580 (1170.3)
Hitch		Welded on
Cutting width	in (m)	73 1/2 (1.87)
Overall width	in (m)	84 3/8 (2.15)
Overall length	in (m)	92 1/4 (2.34)
Cutting height	in (cm)	1 1/2 (3.8) to 18 (45.7) infinitely variable.
Cutting capacity	in (cm)	7 (17.8) Diameter
Spindle hub oil capacity	oz (kg)	85 (2.41)
Spindle hub oil		EP 80-90 wt. gearlube
High volume drive motor	gpm (Lpm)	26-43 (98.4-162.8) flow
Hydraulic pressure	psi (mPa)	Up to 3500 (24.1)
Deck thickness	in (mm)	1/4 (6)
Side skirt construction	in (mm)	1/4 (6) Steel
Deck wear protection		Four, corner-mounted skid shoes
Skid shoe construction	in (mm)	3/8 (10) plate
Blade carrier	in (mm)	(2) Round 1/2 (13) plate weldments
Blade size	in (mm)	3/4 (19) double edge
Blade rotation		Clockwise
Blade bolt		3/4-10 Grade 8
blade tip speed	fpm (mps)	14870 (75.5) at 43 gpm (162.8 Lpm)
Front deck protection		Bi-fold door with single row chain guard
Rear deck protection		Single row chain guard
Deck lift height protection		Height adjustment safety chain
Mulching teeth	in (mm)	3/4 (19) SQ carbide

